



agromaster®

INTERROW CULTIVATOR WITH ROUTER (AMELE)



Interrow Cultivator with Router is an ENVIRONMENTALLY FRIENDLY machine that destroys the weeds existing between the rows of the plants such as (corn, beet, sunflower, cotton, potato, tomato, pepper etc.) that are planted on the rows without damaging the plants and thus ensures that the plants get the adequate nutrients and water from the soil. The row space can be adjusted by sliding the units on the main frames. The working depth is adjusted by the 2 displaceable wheels located on the main frame. The working depth of the units may be different depending on the products and plant space.

Thanks to the optional fertilizer box and the furrow opener apparatus, the fertilizer that has been scattered during the hoeing is made to be mixed with the soil homogenously and after this mixture is piled up towards the plant root the plant benefits hugely from the fertilizer with the middle-breaking procedure.



Contact:

2.Org.San.Böl. Evrenköy Cad. No: 32 42050 Selçuklu Konya / TÜRKIYE

Tel. +90 332 235 64 23 - 24 Fax +90 332 233 75 81

agromaster@agromaster.com | www.agromaster.com



agromaster®

INTERROW CULTIVATOR WITH ROUTER (AMELE)



Technical Specifications*	Units	AMELE 2A	AMELE 3	AMELE 4	AMELE 5	AMELE 6	AMELE 7	AMELE 8
Working Depth	mm	100	100	100	100	100	100	100
Overall Width	mm	2030	2030	2530	3030	2530	4830	3030
Overall Length	mm	1200	1200	1200	1200	1200	1200	1200
Overall Height	mm	1100	1100	1100	1100	1100	1100	1100
Machine Weight	(kg)	370	430	520	620	645	860	900
P.T.O Shaft Rotations	(max) (min-0)	540	540	540	540	540	540	540
Required Tractor Power	HP	25	30	40	60	50	max.60	max.80

*Manufacturer reserves rights to change them without notice.

Contact:

2.Org.San.Böl. Evrenköy Cad. No: 32 42050 Selçuklu Konya / TÜRKIYE

Tel. +90 332 235 64 23 - 24 Fax +90 332 233 75 81

agromaster@agromaster.com | www.agromaster.com